

2.5" External Enclosure

SATA I/II (3.0Gbps) and USB 2.0 (480Mbps) chipset
Direct Storage (Cableless Connector Interface)



Features a mini-USB and eSATA connector with multi-colored LED



Low profile slim case design



Performance

Bus transfer rate (maximum)
-USB2.0 - 480Mbps
-SATA I / II - 1.5Gbps / 3.0Gbps (maximum)



DS-2215SESBK
(SATA to eSATA+USB)

Other Model

DS-2215B2BK
(IDE to USB2.0)

Environmental Specifications

Operating temperature: 5°C to 40°C

Windows System Requirements

Pentium III-class equivalent processor or later
Windows 98SE, ME, 2000, XP, or Vista
CD-ROM drive
512 MB RAM or higher
Available USB 2.0 & eSATA ports

Mac System Requirements

iMac, Power Mac G4 or later models
Mac OS 10.4.x or higher
CD-ROM drive
512 MB RAM or higher
Available USB 2.0 & eSATA ports

Drive Configuration

Support 2.5" SATA I/II Hard Drive

Physical Specifications

Dimensions: 5.3" (L) x 3.2" (W) x 0.5" (H)
Weight: 0.2 lb
Material: Aluminum Frame / Plastic Tray

Power Requirements

AC Input Voltage: 100 ~ 240V/12V-1.7A VAC
Input Frequency: 47 ~ 63 Hz AC
Polarity: In (-), Out (+)

Package Contents

VENUS DS2 - 2.5" Aluminum External Enclosure
User's Manual
Software driver (for USB 2.0/Windows 98SE)
eSATA Data cable
mini USB Data Y-cable
Carrying pouch

